

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 2/13/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : EBO-4200C

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Smart Chemical Solutions, LLC 2708 NE Main St. Ennis, TX 75119 T (806) 367-8031

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3 H226 Flammable liquid and vapor

Acute toxicity (inhalation:dust,mist) Category 4 H332 Harmful if inhaled

Carcinogenicity Category 2 H351 Suspected of causing cancer Hazardous to the aquatic environment - Acute Hazard Category 1 H400 Very toxic to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)









Signal word (GHS US) : Warning

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H332 - Harmful if inhaled

H351 - Suspected of causing cancer H400 - Very toxic to aquatic life

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust, fume, gas, mist, vapors, spray. P271 - Use only outdoors or in a well-ventilated area.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a poison center or doctor if you feel unwell.

P370+P378 - In case of fire: Use media other than water to extinguish.

P391 - Collect spillage.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

43.72% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

43.72% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Solvent Naphtha (petroleum), heavy arom.	CAS-No.: 64742-94-5	41.5 – 73	Flam. Liq. 4, H227 Acute Tox. 3 (Inhalation:dust,mist), H331 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Naphthalene	CAS-No.: 91-20-3	0.25 – 2.75	Flam. Liq. 4, H227 Acute Tox. 3 (Inhalation:dust,mist), H331 Carc. 2, H351 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2,4-Trimethylbenzene	CAS-No.: 95-63-6	0.2 – 2	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if

you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor. Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust, fume,

gas, mist, vapors, spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

2/13/2023 (Issue date) US - en 3/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume, gas, mist,

vapors, spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EBO-4200C

Local name

No additional information available

Solvent Naphtha (petroleum), heavy arom. (64742-94-5)

No additional information available

1,2,4-Trimethylbenzene (95-63-6)

USA - ACGIH - Occupational Exposure Limits

	* * · · · · · · · · · · · · · · · · ·
ACGIH OEL TWA [ppm]	10 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2022

1,2,4-Trimethyl benzene

Naphthalene (91-20-3)

USA - ACGIH - Occupational Exposure Limits

Local name	Naphthalene
ACGIH OEL TWA [ppm]	10 ppm
Remark (ACGIH)	TLV® Basis: URT irr; cararacts; hemolytic anemia. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2022

USA - ACGIH - Biological Exposure Indices

COA - ACOIT - DIOLOGICAL Exposure mulces		
Local name	NAPHTHALENE	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Naphthalene (91-20-3)	
BEI	Parameter: 1-Naphthol + 2-Naphthol (with hydrolysis) - Sampling time: End of shift - Notations: Nq, Ns
Regulatory reference	ACGIH 2022

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Mixture contains one or more component(s) which have the following colour(s):

Colourless

Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of

overexposure.

Mixture contains one or more component(s) which have the following odour:

Aromatic odour

Odor threshold : No data available pH : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available Flash point : No data available response.

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available

Density : 0.95 (0.932 – 0.968) g/cm³

Solubility : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

EBO-4200C	
ATE US (dust, mist)	1.127 mg/l/4h
Unknown acute toxicity (GHS US)	43.72% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 43.72% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

Solvent Naphtha (petroleum), heavy arom. (64742-94-5)	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: RTECS
LC50 Inhalation - Rat (Dust/Mist)	> 0.59 mg/l Source: RTECS
ATE US (dust, mist)	0.5 mg/l/4h

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-Trimethylbenzene (95-63-6)	
LD50 oral rat	6000 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 014 day(s))
LD50 dermal rat	3440 mg/kg (24 h, Rat, Male / female, Read-across, Dermal)
LD50 dermal rabbit	> 3160 mg/kg Source: International Uniform ChemicaL Information Database
LC50 Inhalation - Rat	> 10.2 mg/l air (4 h, Rat, Male / female, Read-across, Inhalation (vapours), 14 day(s))
LC50 Inhalation - Rat (Vapours)	18 mg/l Source: Corporate Solution From Thomson Micromedex
ATE US (oral)	6000 mg/kg body weight
ATE US (dermal)	3440 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	18 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Naphthalene (91-20-3)	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dramal rabbit	> 2000 mg/kg Source: RTECS
LC50 Inhalation - Rat (Dust/Mist)	
,	> 0.59 mg/l Source: RTECS
ATE US (dust, mist)	0.5 mg/l/4h
Skin corrosion/irritation	: Not classified
1,2,4-Trimethylbenzene (95-63-6)	No data available in the literature
pH Serious eye damage/irritation	: Not classified
1,2,4-Trimethylbenzene (95-63-6)	. Not dassilled
	No data available in the literature
pH Recoirectory or akin consistization	: Not classified
Respiratory or skin sensitization Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Naphthalene (91-20-3)	
ARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
1,2,4-Trimethylbenzene (95-63-6)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
1,2,4-Trimethylbenzene (95-63-6)	
NOAEL (oral,rat,90 days)	600 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Date Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,vapor,90 days)	1.8 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-Trimethylbenzene (95-63-6)	
Viscosity, kinematic	0.843 mm²/s (20 °C)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life.

	,	
Solvent Naphtha (petroleum), heavy arom. (64742-94-5)		
LC50 - Fish [1]	45 mg/l Source: IUCLID	
EC50 - Crustacea [1]	0.95 mg/l Source: IUCLID	
EC50 72h - Algae [1]	2.5 mg/l Source: IUCLID	
1,2,4-Trimethylbenzene (95-63-6)		
LC50 - Fish [1]	7.72 mg/l (96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)	
EC50 - Crustacea [1]	6.14 mg/l Source: International Uniform ChemicaL Information Database	
EC50 96h - Algae [1]	2.356 mg/l (ECOSAR, Algae, Fresh water, QSAR)	
Naphthalene (91-20-3)		
LC50 - Fish [1]	45 mg/l Source: IUCLID	
EC50 - Crustacea [1]	0.95 mg/l Source: IUCLID	
EC50 72h - Algae [1]	2.5 mg/l Source: IUCLID	

12.2. Persistence and degradability

1,2,4-Trimethylbenzene (95-63-6)	
Persistence and degradability	Not readily biodegradable in water.
Chemical oxygen demand (COD)	0.44 g O ₂ /g substance

12.3. Bioaccumulative potential

Solvent Naphtha (petroleum), heavy arom. (64742-94-5)		
Partition coefficient n-octanol/water (Log Pow)	2.9 – 6.1 Source: IUCLID	
1,2,4-Trimethylbenzene (95-63-6)		
BCF - Fish [1]	243 (Pimephales promelas, QSAR)	
Partition coefficient n-octanol/water (Log Pow)	3.63 (Experimental value, KOWWIN)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Naphthalene (91-20-3)		
Partition coefficient n-octanol/water (Log Pow)	2.9 – 6.1 Source: IUCLID	

12.4. Mobility in soil

1,2,4-Trimethylbenzene (95-63-6)	
Surface tension	No data available in the literature

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-Trimethylbenzene (95-63-6)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.04 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

DOT	IMDG	IATA
14.1. UN number		
1993	1993	1993
14.2. Proper Shipping Name		
Flammable liquids, n.o.s. (PETROLEUM), HEAVY AROMATIC)	FLAMMABLE LIQUID, N.O.S. (PETROLEUM), HEAVY AROMATIC)	Flammable liquid, n.o.s. (PETROLEUM), HEAVY AROMATIC)
14.3. Transport hazard class(es)		
3	3	3
PLANMAGE LIQUID	3	3
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available	1	1

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1993

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

IMDG

Special provision (IMDG) : 223, 274, 955

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : LP01, P001

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : A

IATA

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y344 : 10L PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) 355 60L PCA max net quantity (IATA) CAO packing instructions (IATA) 366 CAO max net quantity (IATA) 220L Special provision (IATA) A3 ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

1,2,4-Trimethylbenzene CAS-No. 95-63-6 0.2 – 2%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Naphthalene CAS-No. 91-20-3 0.25 – 2.75%

Naphthalene (91-20-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 100 lb

15.2. International regulations

CANADA

Solvent Naphtha (petroleum), heavy arom. (64742-94-5)

Listed on the Canadian DSL (Domestic Substances List)

Naphthalene (91-20-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Solvent Naphtha (petroleum), heavy arom. (64742-94-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Naphthalene (91-20-3)

Listed on IARC (International Agency for Research on Cancer)

Listed as carcinogen on NTP (National Toxicology Program)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H226	Flammable liquid and vapor	
H227	Combustible liquid	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

Nothing contained herein grants or extends a license, express or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be held liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy for furnishing of such information.

The seller makes no warranty expressed or implied concerning the accuracy or any results to be obtained from the use of any information and no warranty expressed or implied concerning the use of the products. The buyer assumes all risks of the use and/or handling.