

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : SCW-3894CB

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Smart Chemical Solutions, LLC
3505 Olsen Blvd
Suite 201
Amarillo, TX 79109
T (806) 367-8031

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Respiratory sensitization, Category 1	H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Acute Hazard Category 1	H400	Very toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412	Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H334 - May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P304+P341 - If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 - Get medical advice/attention if you feel unwell.
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P391 - Collect spillage.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

19.6% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
51.7% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
23.7% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Methanol	CAS-No.: 67-56-1	10.15 – 31.7
1,2-Ethanediol	CAS-No.: 107-21-1	10 – 30
Glutaraldehyde	CAS-No.: 111-30-8	1 – 15

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%
Ethanolamine	CAS-No.: 141-43-5	0.99 – 14.85
Amino Methylene Phosponic Acid Salts	CAS-No.: 7647-01-0	1 – 10
2-Butoxyethanol	CAS-No.: 111-76-2	1 – 5
Imidazoline	CAS-No.: 61790-69-0	1 – 5
Quaternary ammonium compounds, benzyl-C12-16 alkyldimethyl, chlorides	CAS-No.: 68424-85-1	0.8 – 4.1
Benzyl Alkyl Pyrdine	CAS-No.: 68909-18-2	0.8 – 4

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a physician immediately. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause an allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)

USA - ACGIH - Occupational Exposure Limits

Local name	Methanol
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	250 ppm

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)

Remark (ACGIH)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2022

USA - ACGIH - Biological Exposure Indices

Local name	METHANOL
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns
Regulatory reference	ACGIH 2022

USA - OSHA - Occupational Exposure Limits

Local name	Methyl alcohol
OSHA PEL TWA [1]	260 mg/m ³
OSHA PEL TWA [2]	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

1,2-Ethandiol (107-21-1)

USA - ACGIH - Occupational Exposure Limits

Local name	Ethylene glycol
ACGIH OEL TWA [ppm]	25 ppm (Vapor fraction)
ACGIH OEL STEL	10 mg/m ³ (Inhalable fraction, Aerosol only)
ACGIH OEL STEL [ppm]	50 ppm (Vapor fraction)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2022

Ethanolamine (141-43-5)

USA - ACGIH - Occupational Exposure Limits

Local name	Ethanolamine
ACGIH OEL TWA [ppm]	3 ppm
ACGIH OEL STEL [ppm]	6 ppm
Remark (ACGIH)	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2022

USA - OSHA - Occupational Exposure Limits

Local name	Ethanolamine
OSHA PEL TWA [1]	6 mg/m ³
OSHA PEL TWA [2]	3 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection: Protective gloves

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection: Safety glasses

Skin and body protection: Wear suitable protective clothing

Respiratory protection: Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Color	: dark brown
Odor	: slight
Odor threshold	: No data available
pH	: 5.5 – 6.5
Melting point	: Not applicable
Freezing point	: <-10°F
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Toxic in contact with skin.
Acute toxicity (inhalation) : Fatal if inhaled.

SCW-3894CB	
ATE US (oral)	801.322 mg/kg body weight
ATE US (dermal)	752.907 mg/kg body weight
ATE US (dust, mist)	0.26 mg/l/4h
Unknown acute toxicity (GHS US)	19.6% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 51.7% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 23.7% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Methanol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, Aqueous solution, Oral, 7 day(s))
LD50 dermal rabbit	300 mg/kg Source: ECHA
LC50 Inhalation - Rat	128 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	1187 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

1,2-Ethanediol (107-21-1)	
LD50 oral rat	7712 mg/kg body weight (according to BASF-internal standards, Rat, Male / female, Experimental value, Aqueous solution, Oral, 7 day(s))
LD50 dermal	> 3500 mg/kg body weight (Mouse, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 2.5 mg/l (6 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
ATE US (oral)	7712 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h

2-Butoxyethanol (111-76-2)	
LD50 dermal rat	> 2000 mg/kg Source: ECHA

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Butoxyethanol (111-76-2)

ATE US (oral)	500 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h

Ethanolamine (141-43-5)

LD50 oral rat	1089 mg/kg Source: OECD SIDS
LD50 dermal rabbit	2504 mg/kg Source: OECD SIDS
LC50 Inhalation - Rat (Vapours)	> 1487 mg/l Source: ECHA
ATE US (oral)	1089 mg/kg body weight
ATE US (dermal)	2504 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Quaternary ammonium compounds, benzyl-C12-16 alkyldimethyl, chlorides (68424-85-1)

LD50 oral rat	426 mg/kg Source: National Library of Medicine
ATE US (oral)	426 mg/kg body weight

Imidazoline (61790-69-0)

LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity), Remarks on results: other:
---------------	---

Glutaraldehyde (111-30-8)

LD50 oral rat	200 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	0.28 – 0.39 mg/l Source: ECHA
ATE US (oral)	200 mg/kg body weight
ATE US (gases)	100 ppmV/4h
ATE US (vapors)	0.28 mg/l/4h
ATE US (dust, mist)	0.05 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 5.5 – 6.5

Amino Methylene Phosponic Acid Salts (7647-01-0)

pH	0.1 (3.65 %)
----	--------------

Ethanolamine (141-43-5)

pH	12.1 Source: ECHA
----	-------------------

Serious eye damage/irritation : Causes serious eye damage.
pH: 5.5 – 6.5

Amino Methylene Phosponic Acid Salts (7647-01-0)

pH	0.1 (3.65 %)
----	--------------

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanolamine (141-43-5)

pH	12.1 Source: ECHA
Respiratory or skin sensitization	: May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-Butoxyethanol (111-76-2)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Causes damage to organs.

Methanol (67-56-1)

STOT-single exposure	Causes damage to organs.
----------------------	--------------------------

Glutaraldehyde (111-30-8)

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

Glutaraldehyde (111-30-8)

LOAEC (inhalation, rat, gas, 90 days)	0.25 ppm Animal: rat, Remarks on results: other:
NOAEL (dermal, rat/rabbit, 90 days)	150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Guideline: EPA OPPTS 870.3250 (Subchronic Dermal Toxicity 90 Days)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

1,2-Ethandiol (107-21-1)

Viscosity, kinematic	No data available in the literature
----------------------	-------------------------------------

Benzyl Alkyl Pyrdine (68909-18-2)

Viscosity, kinematic	≈ 48 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'
----------------------	--

Glutaraldehyde (111-30-8)

Viscosity, kinematic	12.75 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'
Symptoms/effects after inhalation	: May cause an allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.
-------------------	--

Methanol (67-56-1)

LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
EC50 96h - Algae [1]	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
1,2-Ethanediol (107-21-1)	
LC50 - Fish [1]	> 72860 mg/l (EPA 600/4-90/027, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 96h - Algae [1]	6500 – 13000 mg/l Source: ECHA
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
2-Butoxyethanol (111-76-2)	
LC50 - Fish [1]	1474 mg/l Source: ECHA
EC50 - Crustacea [1]	1800 mg/l Source: ECHA
EC50 72h - Algae [1]	911 mg/l Source: ECHA
Ethanolamine (141-43-5)	
LC50 - Fish [1]	170 mg/l Source: OECD SIDS
EC50 - Crustacea [1]	32.6 mg/l
ErC50 algae	2.1 mg/l Source: ECHA
Benzyl Alkyl Pyrdine (68909-18-2)	
LC50 - Fish [1]	14.1 mg/l Test organisms (species): Cyprinodon variegatus
EC50 - Crustacea [1]	3.1 mg/l Source: ECHA Chem
EC50 72h - Algae [1]	0.47 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.16 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	0.16 mg/l Source: ECHA Chem
Quaternary ammonium compounds, benzyl-C12-16 alkyldimethyl, chlorides (68424-85-1)	
LC50 - Fish [1]	0.51 mg/l Source: The ECOTOXicology database
EC50 - Crustacea [1]	0.0059 mg/l Source: The ECOTOXicology database
EC50 96h - Algae [1]	4.813 mg/l Source: Ecological Structure Activity Relationships
Imidazoline (61790-69-0)	
LC50 - Fish [1]	4.138 mg/l Source: ECOSAR
EC50 72h - Algae [1]	> 10 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	0.328 mg/l Source: ECOSAR
Glutaraldehyde (111-30-8)	
LC50 - Fish [1]	0.8 mg/l Source: ECHA
EC50 72h - Algae [1]	1.2 mg/l Source: ECHA

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance

1,2-Ethandiol (107-21-1)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.47 g O ₂ /g substance
Chemical oxygen demand (COD)	1.24 g O ₂ /g substance
ThOD	1.29 g O ₂ /g substance

Amino Methylene Phosponic Acid Salts (7647-01-0)	
Persistence and degradability	Biodegradability: not applicable.

12.3. Bioaccumulative potential

Methanol (67-56-1)	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

1,2-Ethandiol (107-21-1)	
Partition coefficient n-octanol/water (Log Pow)	-1.36 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.

2-Butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 Source: ECHA

Amino Methylene Phosponic Acid Salts (7647-01-0)	
Bioaccumulative potential	Not bioaccumulative.

Ethanolamine (141-43-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.31 Source: ICSC

Benzyl Alkyl Pyrdine (68909-18-2)	
Partition coefficient n-octanol/water (Log Pow)	0.3 – 3.93 Source: ECHA Chem

Quaternary ammonium compounds, benzyl-C12-16 alkyldimethyl, chlorides (68424-85-1)	
Partition coefficient n-octanol/water (Log Pow)	3.91 Source: Quantitative Structure Activity Relation

Glutaraldehyde (111-30-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.36 Source: ECHA

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

Methanol (67-56-1)

Mobility in soil	2.75 Source: HSDB
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

1,2-Ethandiol (107-21-1)

Mobility in soil	0.2 Source: HSDB
Surface tension	48.4 mN/m (20 °C)
Ecology - soil	Highly mobile in soil.

Amino Methylene Phosponic Acid Salts (7647-01-0)

Ecology - soil	No (test)data on mobility of the component(s) available. May be harmful to plant growth, blooming and fruit formation.
----------------	--

Benzyl Alkyl Pyrdine (68909-18-2)

Mobility in soil	17.7827941 – 251188.64315096 Source: ECHA Chem
------------------	--

Quaternary ammonium compounds, benzyl-C12-16 alkyldimethyl, chlorides (68424-85-1)

Mobility in soil	1002 Source: EPI Suite
------------------	------------------------

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.




SECTION 14: Transport information

DOT	IMDG	IATA
14.1. UN number		
1993	1993	1993
14.2. Proper Shipping Name		
Flammable liquids, n.o.s. (Methanol)	FLAMMABLE LIQUID, N.O.S. (Methanol)	Flammable liquid, n.o.s. (Methanol)
14.3. Transport hazard class(es)		
3	3	3

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	IMDG	IATA
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available		

14.6. Special precautions for user

DOT	
UN-No.(DOT)	: UN1993
DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
IMDG	
Special provision (IMDG)	: 223, 274, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : A

IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provision (IATA) : A3
ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

1,2-Ethanediol	CAS-No. 107-21-1	10 – 30%
2-Butoxyethanol	CAS-No. 111-76-2	1 – 5%
Amino Methylene Phosponic Acid Salts	CAS-No. 7647-01-0	1 – 10%
Ethanolamine	CAS-No. 141-43-5	0.99 – 14.85%
Benzyl Alkyl Pyrdine	CAS-No. 68909-18-2	0.8 – 4%
Quaternary ammonium compounds, benzyl-C12-16 alkyldimethyl, chlorides	CAS-No. 68424-85-1	0.8 – 4.1%
Imidazoline	CAS-No. 61790-69-0	1 – 5%
Glutaraldehyde	CAS-No. 111-30-8	1 – 15%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methanol	CAS-No. 67-56-1	10.15 – 31.7%
----------	-----------------	---------------

Methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ : 5000 lb

15.2. International regulations

CANADA

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

SCW-3894CB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

Methanol (67-56-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



WARNING:

This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases

H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA